



F&B Divosan Hypochlorite

VT3

Terminal disinfectant, hypochlorite based

Description

Divosan Hypochlorite is a highly effective oxidising disinfectant based on sodium hypochlorite for use in the food, beverage and dairy industries.

Key properties

- Divosan Hypochlorite is a concentrated sodium hypochlorite solution containing additional stabilising agents to extend storage-life and effectiveness. It is a highly effective disinfectant against all types of micro-organisms including bacteria, yeasts, fungi, spores and viruses.
- Divosan Hypochlorite is used as a terminal disinfectant in both open and closed plant (CIP) systems. It also has excellent deodorising and stain removal properties.
- Divosan Hypochlorite is suitable for manual, soak and spray application in open plant cleaning and also for automatic dosing for CIP.

Benefits

- Highly cost-effective terminal disinfectant for food industry use.
- Broad spectrum disinfectant activity.
- Powerful oxidising action also assists stain removal and deodorises.
- Non-foaming and free-rinsing.
- Effective in soft or hard water.

Use instructions

Dosing should be done in potable water - 4.2 ppm as product Cooling Water, for pool treatment, 20 ppm. Always rinse thoroughly after use. For specific details, please refer to individual method cards.

If more information about the proper dosing amount is needed, please contact the Divergard water consultant.





F&B Divosan Hypochlorite

VT3

Technical data

Appearance: Clear, pale green liquid

pH (1% solution at 20°C): 11

Relative density (20°C): 1.16-1.2

Chemical Oxygen Demand (COD): None

Nitrogen Content (N): None

Phosphorous Content (P): None

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Store in original closed containers or (where applicable) in approved bulk tank, away from sunlight and extremes of temperature. Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.

Product compatibility

Divosan Hypochlorite when applied at the recommended concentration and temperature is suitable for use on the grades of stainless steel commonly found in the processed food industry. It is unsuitable for use on cuprous materials and on soft metals such as aluminium. Always rinse surfaces thoroughly after use (within 1 hour). In the event of uncertainty, it is advisable to evaluate individual materials before any prolonged use.

Test method

Reagents:

0.1 N Sodium thiosulphate

Potassium iodide (10%)

Sulphuric or phosphoric acid (25%)

Procedure:

Add 5 ml Potassium iodide to 100 ml of the test solution. Add 5 ml Sulphuric or Phosphoric acid and titrate with Sodium thiosulphate until the solution is straw yellow in colour. Add approx. 1 ml starch indicator and continue to titrate to a colourless end point.

Calculation:

Available chlorine (ppm) = titre x 35.5

Microbiological data

EN 1276: passed at 0.25% dilution in hard water (300 ppm as CaCO₃), low soil (0.03% bovine albumin) and 5 minutes contact time.

EN 1650: passed at 1% dilution in hard water (300 ppm as CaCO₃), low soil (0.03% bovine albumin) and 15 minutes contact time.

Available pack sizes

Article code & Pack size

7509362 - 20L

7509363 - 200L

7509367 - 950L

7509371 - Bulk



F&B **Divosan Hypochlorite**

VT3