

TASKI® Jontec Forward/SD/ J-Flex/QS/ID

Alkaline floor cleaner, low foam

Description

Heavy duty, alkaline floor cleaner specifically developed for use in scrubber driers. Its low foaming formula removes heavy soil, dirt and grease from all water resistant, non protected hard floors (except unsealed wood). Also ideal for top stripping.

Key properties

- Effective combination of surfactants and alkaline chemicals
- Good emulsifying power
- Low foaming, fast acting
- Versatile application
- Fresh fragrance
- Formulated to prepare floors for top coating

Benefits

- Very good cleaning performance on all types of water resistant hard floors (except unsealed wood)
- Effectively cleans and removes dirt, grease and maintenance product buildup
- Ideal for use in scrubber driers
- Also suitable for single disc machines and wet mopping systems
- Leaves a pleasant, fresh odour
- Excellent top stripper, enables better adhesion of additional coats

Use instructions

Dosage:

TASKI Jontec Forward is available in various pack sizes and is either dosed manually (standard concentrate) or through one of our dispensing systems (SmartDose, J-Flex, QuattroSelect, IntelliDose). For detailed information regarding the specific dosing equipment, please refer to the technical data table. Proper dosage saves costs and minimises environmental impact.

Application

Manual:

Dose/dilute product into a bucket filled with water and apply the solution. Allow to act (do not allow the solution to dry) and scrub, then remove the soiled solution.


Machine:

Dose/dilute product into the full water tank and apply the solution. Allow to act (do not allow the solution to dry) and scrub, then remove the soiled solution.

Top stripping:

Dose/dilute product into a bucket filled with water, in the water tank of the single disc machine/scrubber drier. Apply the solution, leave to act for 5 minutes, scrub and remove soiled solution. Rinse with clear water.

F4h



© A.I.S.E.

TASKI[®] Jontec Forward /SD/Jflex/QS/ID F4h

Alkaline floor cleaner, low foam

Technical data

Platform	SKU	Description/Pack size	Bucket	Scrubber drier	Appearance	pH value neat	pH value in-use	Relative density (20°C)
Standard concentrate	7513111 7513109	TASKI Jontec Forward 1 x 10 L TASKI Jontec Forward 2 x 5 L	25-250ml / 5L (0,5 to 5%)	50-200 ml /10 L (0,5 to 2%) 200 ml/10 L (2% Top stripping)	Clear, colourless	10	8,7 (1%)	1.05 g/cm ³
SmartDose	7520206 7520208	TASKI Jontec Forward SD 1 x 1,4 L	0,2% (70 of 10 L bucket) : 1 pump	0,2% to 0,4% (17 to 35 of 20 L tank) : 1 pump	Clear, colourless	10	8,7 (1%)	1.05 g/cm ³
Intellidose	7515722 7518324	TASKI Jontec Forward ID 2 x 1,5 L	N/A	0,2%, 0,3%, 0,5%	Clear, colourless	10	8,7 (1%)	1.05 g/cm ³
Jflex	7512206 7512205 7512210	TASKI Jontec Forward J-flex 1 x 1,5 L TASKI Jontec Forward J-flex 1 x 1,5 L TASKI Jontec Forward J-flex 1 x 5 L	0,2 to 0,5% (60 to 150 /5 L bucket) 0,2 to 0,5% (60 to 150 /5 L bucket) 0,2 to 0,5% (200 to 500/5 L bucket)	0,2 or 0,5% (15 to 37,5 of 20 L tank) 0,2 or 0,5% (15 to 37,5 of 20 L tank) 0,2 or 0,5% (50 to 125 of 20 L tank)	Clear, light, yellow	11	8,5 (0,5%)	1.03 g/cm ³
Quattro Select	7517107	TASKI Jontec Forward QS 2 x 2,5 L	0,2 to 0,4%	0,2 to 0,4% 0,4% (top stripping)	Clear, light, yellow	11	8,5 (0,5%)	1.03 g/cm ³

The above data is typical of production and should not be taken as specification.

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet (SDS). <https://sds.sealedair.com/>
Only for professional users/specialists. Store in original closed containers away from extremes of temperature.

Product compatibility

Test material compatibility in a small inconspicuous area before use. Immediately remove any solution splashes from alkali-sensitive surfaces (e.g. wooden baseboards, painted/varnished surfaces) with a wet cloth. Do not use on water-sensitive floors, e.g. unsealed wood or cork.